

# **SCT SERIES USER INFORMATION**

## **! CAUTION POWERFUL MAGNETS!**

This product contains a magnetic field and should be kept at a safe distance from electrical equipment, pacemakers, metallic implants, credit cards, and computer equipment.

### **-TOW ATTACHMENT**

Select the appropriate tow attachment for use behind selected vehicle, which must be capable of maintaining a steady 8mph or less.

### **-TOWBAR HEIGHT**

The tow-bar is adjustable for height, by loosening the clamping bolts at the root of the tow-bar, it can be moved up or down, then re-tightened when in the correct position. The optimum position is for the sweeper to be parallel to the ground when attached to the towing vehicle.

### **-GROUND CLEARANCE ADJUSTMENT**

There are axle plates on the side of the sweeper which have alternate holes, to allow for height adjustment. This is to give extra ground clearance for uneven terrain, or if larger objects are being collected. Remove pin from axle, slide wheel off, unbolt axle plate and move to alternate holes as required, then, re-assemble.

### **-RELEASE AND MAGNET LOCK**

There is a large lever on the side of the magnetic sweeper, simply pull this to release the waste from that has been collected. Use the latch on top of the magnetic sweeper to lock the magnets in the off position, then, tow the sweeper away from the waste.

### **-TRANSPORT**

When transporting the magnetic sweeper, use an appropriate pallet, and leave the magnets on/unlatched.

